ADC-CSVR126-16CH

SPECIFICATIONS

RECORDING CHANNELS Up to 16 cameras

VIDEO INPUT 16 channels @ 1080p

INCOMING BANDWIDTH 160 Mbps

OUTGOING BANDWIDTH 256 Mbps

HDMI MAX OUTPUT 4K (3840 x 2160) 60 Hz

VGA MAX OUTPUT Full HD (1920 x 1080) 60 Hz

LOCAL DISPLAY CAPABILITIES Live View, Playback, Clip Export

COMPATIBLE CAMERAS

ADC-V522IR, ADC-V622, ADC-V722W, ADC-VC725, ADC-VC726, ADC-VC736, ADC-VC825, ADC-VC826, and ADC-VC836

SPEED CONTROL

1x, 4x, 8x

HARD DISK DRIVE (HDD) 2 SATA interfaces, up to 8 TB per interface

ETHERNET CONNECTION RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface

USB INTERFACE 1 x USB 2.0; 1 x USB 3.0

POWER ADAPTER 12 V DC ≤ 40 W

DIMENSIONS (W x D x H) 15.2 x 12.4 x 2.0" (385 x 315 x 52 mm)

OPERATING TEMPERATURE 14°F - 131°F (-10°C - 55°C)

OPERATING HUMIDITY 10% - 90% (non-condensing) RH

WEIGHT (WITHOUT HDD) ≤2.2 lbs. (1 kg)

INSTALLATION Rack-mount (1U) compatible

www.alarm.com

© 2018 Alarm.com. All rights reserved.



Stream Video Recorder

Designed specifically to work with the Alarm.com hosted video service, the ADC-CSVR126 Stream Video Recorder provides a 24x7 professional solution for commercial-grade local video storage. With the Stream Video Recorder, you can associate up to 16 Alarm.com video cameras for continous recording.

FEATURES

- Continously records up to 16 Alarm.com video camera streams for local storage on two hard drives
- Rack-compatible (1U), commercial industrial design
- HDMI and VGA output
- 1080p and 4K display option
- USB mouse control
- Works with the Alarm.com website and app for remote viewing of recordings

INCLUDED ACCESSORIES

- Stream Video Recorder
- Power Adapter
- Quick Start Guide
- USB Mouse

LED GUIDE

	-	LED STATUS	DESCRIPTION
POWER	0 -	Solid Green	Powered on
		Off	Powered down
STATUS	0 -	Flashing <mark>Red</mark>	Active
		Off	Idle
NETWORK (TX / RX)	0 -	Flashing Green	Active intranet connection
		Off	No active intranet connection