



Fire Ratings

Type	A	B	C	MED
KS 2 ST	—	34	—	—
KS 5 ST	—	89	—	⊙
KS 5 ST with strap	—	89	—	⊙
KS 2 SBS	—	34	—	⊙
KS 2 SBS with wire bracket	—	34	—	⊙
KS 5 SE	—	89	—	⊙
KS 5 AM	—	89	—	—

- Pull the metal **safety pin A**.
- Pressing the **lever B** opens the **valve C**.
- Carbon dioxide is travelling through the **driptube D** and valve into the **hose E** and the **horn F** for spraying.

- Included standard wall hanger.
- KS 2 ST - wire bracket available separately.
- KS 5 ST - optionally with powder painted metal strap to hold on the standard wall bracket.
- Approved to use on electrical installations up to 1000 V at minimum distance 1 m.

AREAS OF USE

- IT-centres
- Laboratories
- Industrial plants
- Storages with combustible liquids
- Marine industry



GLORIA KS 2 SBS with standard wall hanger

Type	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Qty of extinguishing agent [kg]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	H/W/D in bracket, Ø [mm]
KS 2 ST	K 2	002041.0000	≈6,5	CO ₂	2	CO ₂	8,5	3	-30 / +60	590 / 250 / 120, 104
KS 5 ST	K 5	002031.0000	≈14,5	CO ₂	5	CO ₂	13,5	4-5	-30 / +60	930 / 400 / 150, 136
KS 5 ST with strap	K 5	002031.1790	≈14,5	CO ₂	5	CO ₂	13,5	4-5	-30 / +60	690 / 400 / 150, 136
KS 2 SBS	K 2	001831.0000	≈5,4	CO ₂	2	CO ₂	8,5	3	-30 / +60	513 / 265 / 170, 117
KS 2 SBS with wire bracket	K 2	001831.3007	≈5,4	CO ₂	2	CO ₂	8,5	3	-30 / +60	513 / 265 / 170, 117
KS 5 SE	K 5	001821.0000	≈12,5	CO ₂	5	CO ₂	13,5	4-5	-30 / +60	700 / 480 / 160, 152
KS 5 AM	K 5	001821.1683	≈12,5	CO ₂	5	CO ₂	13,5	4-5	-30 / +60	700 / 480 / 160, 152

GLORIA KS 2 ST / KS 5 ST / KS 2 SBS / KS 5 SE / KS 5 AM - technical data
subject to technical changes